



6602W

ICONA MONITOR, VIP H264



Flush-mounted (on box Art. 6117) or surface-mounted (with bracket Art. 6620) colour monitor with audio induction loop, 4.3" / 16:9 touch screen and hands-free full-duplex audio. Allows adjustment of backlighting intensity, contrast, audio volume and ringtone volume. Equipped as standard with sensitive touch controls for lock-release, audio activation, self-ignition, privacy service and 3 other controls for programmable functions, and door open and new message indicator LEDs. Standard floor door call and call repetition management, with alarm and panic inputs and micro SD Card slot. You can customise the ringtone and video memory function with an absent message. Can also be used on standard POE systems. Dimensions 142.5x147x23mm. Compatible with H.264 video format.

AWARDS





6602W

ICONA MONITOR, VIP H264

GENERAL DATA

Product height (mm)	147
Product width (mm)	143
Product depth (mm)	23
Product weight (g)	500
Product color	White RAL9003, base grey RAL7001
Material	ABS, Glass
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory
Desk base-mounted	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

ViP	Yes
-----	-----

DISPLAY FEATURES

Size (inches) (")	4.3
Aspect Ratio	16:9
Touch screen	Yes, resistive
Resolution (pixels)	480x272
OSD menu	Yes

AUDIO FEATURES

Type	Hands-free
Induction loop function	Yes
Microphone	6mm (Ø), Omnidirectional
Loudspeaker	40 (ø) x 20 (H)mm, 8 ohm, 2W
Technologies implemented	Full-Duplex



6602W

ICONA MONITOR, VIP H264

ELECTRICAL CHARACTERISTICS

Type of power supply	PoE
PoE power supply	Standard IEEE 802.3af, Comelit PoE (56VDC)

HARDWARE FEATURES

Type of buttons	Capacitive
Service buttons	Lock-release, Answer, Silent (Privacy), Menu, Messages, Door open
No. of programmable buttons for additional functions	3
Clamps	Out1 V- Pan AI V- CFP Op- Op+ S- S+
Removable terminals	Yes
Number of inputs (n°)	3
Number of outputs (n°)	1
Memory card supported	Micro-SD (not supplied)
Communication ports	RJ45 (Ethernet)

SETTINGS

Loudspeaker volume	Yes
Ringtone volume	Yes
Screen contrast	Yes
Screen backlight	Yes

NETWORK AND COMMUNICATION PROTOCOLS

Type of LAN network	Ethernet 10/100 Mbit/s, IEEE 802.3, IEEE 802.3u (Fast Ethernet)
IP address assignment	Auto IP, DHCP, Static

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree	IP30
Operating temperature (°C)	5 ÷ 40
Operating humidity (RH max - %) (%)	25 ÷ 75



6602W

ICONA MONITOR, VIP H264

ENVIRONMENTAL AND COMPLIANCE FEATURES

Environmental class	I
Compliance and Certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS


Door opener	Yes
Self Activation	Yes
Intercom calls	Yes
Actuator control	Yes
Outside door call input	Yes
Output for call repetition	Yes
Silent mode (Privacy)	Yes
Video memory	Yes
Door opening on call (Doctor)	Yes
Door open signaling	Si
Multiple address	Yes
Customisable ringtone	Yes
Sending alarm calls	Yes
Receiving ViP messages	Yes



6602W

ICONA MONITOR, VIP H264

ACCESSORIES



6612A **DESK BASE FOR ICONA MONITOR**

Desk base installation accessory for Icona monitor. Dimensions 105x70x110mm.



6617 **Flush-mounted box for plasterboard. Icona**

Flush-mount box allowing mounting of Icona series monitors on plasterboard and/or cement walls. Dimensions: 129x129x50 mm



6620 **WALL BRACKET FOR ICONA MONITOR**

Wall bracket for Icona monitor. Colour: White. Dimensions: 136.6x141.6x13.8mm.



6118 **MAXI, PLANUX, SMART, ICONA CLIPS FOR DRYWALL**

Installation kit for drywall for Maxi, Planux, Smart and Icona monitors.



6117 **PLANUX, SMART, ICONA FLUSH BACKBOX**

Flush mounted box for Planux, Smart and Icona monitors Dimensions: 132x132x50mm